

# CERTIFICATE

Issued to:  
Applicant:  
**Eaglerise Electric & Electronic (China) Co., Ltd.**  
No. A3, Guicheng Sci-Tech Industrial Park,  
Jianping Road, Nanhai District,  
Foshan City, Guangdong Province, China

Licensee:  
**Eaglerise Electric & Electronic (China) Co., Ltd.**  
Beijiao Branch  
No.4, East Huanzhen Road,  
Beijiao Shunde,  
528000 Foshan, Guangdong, China

Product : LED driver  
Trade name(s) : EAGLERISE  
Type(s)/model(s) : FLS-30-750 LA

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard EN 61347-1:2015, EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017, EN 62384:2006 and EN 62384:2006/A1:2009
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 4324517

DEKRA hereby grants the right to use the KEMA-KEUR certification mark.

The KEMA-KEUR certification mark may be applied to the product as specified in this certificate for the duration of the KEMA-KEUR certification agreement and under the conditions of the KEMA-KEUR certification agreement.

This certificate is issued on 4 March 2018 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 35-102987

DEKRA Certification B.V.



drs. G.J. Zoetbrood  
Managing Director



Rosa Zhou  
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE  
DUTCH ACCREDITATION  
COUNCIL



**SPECIFICATION OF THE CERTIFIED PRODUCT****Product data**

Product	: LED driver
Trade name(s)	: EAGLERISE
Type(s)/model(s)	: FLS-30-750 LA
Rated voltage	: 220-240 V~
Rated frequency	: 50/60 Hz
Rated wattage	: 39,2 W MAX
Rated current	: 0,24 A MAX
Output current	: 500-750 mA
Output voltage range	: 24-42 Vdc
Max. output wattage	: 31,5 W MAX
Class of insulation	: Class II
Power factor	: $\geq 0,95$
Degree of protection	: IP20
Ambient temperature (ta)	: 50 °C
Max. case temperature (tc)	: 90 °C

**TESTS****Test requirements**

EN 61347-1:2015  
EN 61347-2-13:2014  
EN 61347-2-13:2014/A1:2017  
EN 62384:2006  
EN 62384:2006/A1:2009

**Test result**

The test results are laid down in DEKRA test file 434162500.

**Additional information**

This certificate replaces certificate No. 35-102805 which we herewith declare invalid.

The list of components is laid down at test report 4341625.50.

**Conclusion**

The examination proved that all requirements were met.

**Factory location**

Eaglerise Electric & Electronic (China) Co., Ltd. Beijiao Branch  
No.4, East Huanzhen Road,  
Beijiao Shunde,  
528000 Foshan, Guangdong, China

Trade name(s) : EAGLERISE stands for

