


MH-S series (1/1.8"3MP)

- Support up to 1/2" camera sensors ;
- 9 models , focal length covering from 4mm to 75mm ;
- High resolution for 3 MP camera in full of view ;
- Lower distortion design ;
- Small size structure suitable for system integration and installation ;
- Stable sharpness quality when temperature varies from -20°C ~ 50°C ;



| Model | | MH0420S | MH0620S | MH0820S | MH1220S |
|-----------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Focal Length | | 4mm | 6mm | 8mm | 12mm |
| Image Circle | | Φ9mm | Φ9mm | Φ9mm | Φ9mm |
| F# | | F2.0 - C | F2.0 - C | F2.0 - C | F2.0 - C |
| Angle of View | 1/1.8"(7.2x5.3mm) | 94.0°×82.9°×66.5° | 69.8°×59.6°×46° | 56°×47.2°×36.0° | 40.7°×33°×24.3° |
| | 1/2"(6.4x4.8mm) | 88.3°×76.5°×61° | 63.7°×53.2°×41.1° | 51.3°×42.3°×32.4° | 36.3°×29.5°×22.4° |
| Working Distance | | 0.1m to inf | 0.1m to inf | 0.1m to inf | 0.1m to inf |
| TV Distortion | | - 0.66% | - 0.10% | - 0.10% | - 0.10% |
| Relative Illumination | Full Aperture | 43% | 52% | 55% | 41% |
| | F4.0 | 69% | 72% | 66% | 50% |
| Mount | | C- Mount | C- Mount | C- Mount | C- Mount |
| Dimensions | | 30.89mm×Φ38.2mm | 23.5mm×Φ26.8mm | 25mm×Φ26.8mm | 19.9mm×Φ26.8mm |
| Filter Thread | | No | M25.5×P0.5 | M25.5×0.5 | M25.5×P0.5 |
| Weight | | 32g | 32g | 32g | 28.5g |
| Working Temperature | | - 20°C~50°C | - 20°C~50°C | - 20°C~50°C | - 20°C~50°C |