

PRO Series Specification

# C8200



## 48V-10mm

---



## 【General description】

- Double leds per cut for 48V, easily for customized application
- Parameter matches with traditional ones,better for stock management
- Self-encapsulated design offers 5 optional 2300-6000K white lights
- With life span over 60000H
- Ta: -25-40°C; Tc: 75°C(max)



## 【Dimension】

Input voltage: DC48V

CRI: 90

Max.power: 13.2W(1m)

Power range: 10.8~13.2W(1m)

Rated current: 0.25A(1m)

Typical Power: 12W(1m)

tape IP: IP20/IP65/IP67

On-off times: 10000 (test times)

Warranty: 5years

Max.length: 15000mm(49.2')



Cutting unit: 2leds/10mm(0.39")

LED pitch: 5mm(0.19")

Min. bend diameter:  $\Phi$ 60mm(2.36")

Mounting: 3M tape


Copper foil: 3oz




## 【Photo-electric Parameters】

CRI	Color	CCT	Lumen(lm/m)	Lumen(lm/ft)	lm/W	ErP 2019
Ra>90	SW	2700K	1595	486	133	E
Ra>90	WW	3000K	1700	519	142	E
Ra>90	PW	3500K	1690	515	141	E
Ra>90	NW	4000K	1715	523	143	E
Ra>90	W	6000K	1595	486	133	E

- 1.The tolerance of output data can be vary up to 15%.
- 2.the output data tested according to IES TM-30-15.
- 3.the output data is based on IP20/1merter, data of 5m in only for reference.
- 4.IP protection process leads changes to size, CCT and luminous flux.







### 【IP process information】














Remark: IP20 strip have two kinds of wire, PVC wire is used for UL strip , and parallel wire is used for non-UL strip.

## 【Electronic & output data】


IP Process	Picture	Picture description	Size	optional CCT/color for finished product	lumen output rate
NO	 NO/IP20	No proof	10mm*1.5mm	2700K/3000K/3500K/4000K/6000K	100%
NA	 NANO/IP65	Nano-proof	10mm*1.6mm	2700K/3000K/3500K/4000K/6000K	98%
ET	 ET/IP67	Extrusion tube	12mm*4.8mm	2700K/3000K/3500K/4000K/6000K	88%
ETS	 ETS/IP65	Extrusion tube	12mm*4.8mm	2700K/3000K/3500K/4000K/6000K	88%

## 【Accessories Information】


Name	Picture	Code	coding	description
Fixed Clip		94-02-00-0003	FSW10SA	Silicone clip, screw: PA 3*8mm, suitable for 10mm FPC,EF/ET strip
Silicone Plug Kit		94-02-00-0046	DT10EA-A	Silicone plug kit is suitable for 10mm board width, ET/EF series silicone extrusion light strip
Silicone stopper kit		94-02-00-0047	DW10EA-A	Silicone tail plug kit is suitable for 10mm board width, ET/EF series silicone extrusion light strip
Mounting groove		94-02-00-0025	CVT10EA-14100100	Transparent PVC mounting groove,suitable for 10mm FPC,silicone extruded EF/ET strip
Stopper glue		94-16-03010001	AS-PG-0003	Silicone gel,suitable for ET/EF/EG waterproof LED strip
ET solderless plug		94-03-00-0030	PT210-ETWA	Monochromatic light strip, 10mm board width, ET protection technology
ET press-fit terminals		94-03-00-0031	CBX210-ETWA020	Monochromatic light strip, 10mm board width, ET protection technology
ET press-fit terminal kit		94-03-00-0032	STBX210-ETWA020	Monochromatic light strip, 10mm board width, ET protection technology
Connector for wire and FPC		/	CXB210-DFTA	2PIN,wire to board(without wire),suitable for 10mm single color IP20 strips
Connector for FPC and FPC		/	CBB210-DFTA	2PIN,board to board,suitable for 10mm single color IP20 strips
L-connector for FPC and FPC		/	CBBL210-DFTA	2PIN,board to board(L shape),suitable for 10mm single color IP20 strips

## 【Packing】

Colors brand package



General customized package



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	5000*10*1.5	5	250	0.161	8.05	9.257	41*41*26
NA	5000*10*1.6	5	250	0.164	8.2	9.43	41*41*26
ET	5000*12*4.8	5	200	0.511	20.44	23.506	41*41*26
ETS	5000*12*4.8	5	200	0.5	20	23	41*41*26

Remark: data with 10% tolerance

### · Engineering packaging of ET(IP67)

(free-soldering end caps with 40 cover per box could be ordered separately if needed)



### · Engineering packaging of NO(IP20)/NA(IP65).



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	50000*10*1.5	50	500	1.61	16.1	18.515	41*41*26
NA	50000*10*1.6	50	500	1.64	16.4	18.86	41*41*26
ET	50000*12*4.8	50	100	5.21	10.42	11.983	25.5*25.5*26
ETS	50000*12*4.8	50	100	5.21	10.42	11.983	25.5*25.5*26

Remark: data with 10% tolerance

### **【Precautions】**

- Please drive the led strip with 48VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -25℃ -40℃. Storage temperature: 0℃ -60℃. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.