


Toning Series Specification

D560RGBW




24V-12mm








【IP process information】



【Electronic & output data】


IP Process	Picture	Picture description	Size	optional CCT/color for finished product	lumen output rate
NO		No proof	12mm*2.1mm	RGBW	100%
NA		Nano-proof	12mm*2.1mm	RGBW	98%
ET		Extrusion tube	14mm*4.8mm	RGBW	88%

【Accessories Information】

Name	Picture	Code	description
Fixed Clip		94-02-00-0004	Silicone clip, screw: PA 3*8mm, suitable for 12mm FPC,EF/ET strip
Gas phase rubber plug		94-02-00-0048	Silicone cap with hole&without hole, suitable for 12mmFPC, ET waterproof LED strip
Gas phase gel plugging		94-02-00-0049	Silicone end cap with hole&without hole, suitable for 12mmFPC, ET waterproof LED strip
Stopper glue		94-16-03010001	Silicone gel,suitable for ET/EF/EG waterproof LED strip
Mounting groove		94-02-00-0026	Transparent PVC mounting groove,suitable for 12mm FPC,silicone extruded EF/ET strip

[Packing]

Colors brand package



General customized package




IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	5000*12*2.1	5	250	0.147	7.35	8.453	41*41*26
NA	5000*12*2.1	5	250	0.15	7.5	8.625	41*41*26
ET	5000*14*4.8	5	150	0.587	17.61	20.252	41*41*26

Remark: data with 10% tolerance

· Engineering packaging of NO(IP20)NA(IP65)

(free-soldering end caps with 40 cover per box could be ordered separately if needed)



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	50000*12*2.1	50	500	0.147	14.7	16.905	41*41*26
NA	50000*12*2.1	50	500	0.15	15	17.25	41*41*26

Remark: data with 10% tolerance

【Precautions】

- Please drive the led strip with 24VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -25°C~40°C. Storage temperature: 0°C~60°C. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.