

DAISY-7X1-W-D

~50° wide beam. Variant with diffused lenses.

TECHNICAL SPECIFICATIONS:

Dimensions	279.5 x 39.6 mm
Height	20.3 mm
Fastening	pin, screw, clips
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
C17362_DAISY-7X1-W-D	Linear lens	PMMA	milky	
C16872_DAISY-7X1-SHD	Shade	PC	black	gloss
C16876_DAISY-7X1-SHD-WHT	Shade	PC	white	gloss
C17051_DAISY-7X1-SHD-MATT	Shade	PC	black	matt
C17225_DAISY-7X1-SHD-WHT-MATT	Shade	PC	white	matt
C17533_DAISY-7X1-SHD-MET-MATT	Shade	PC	metal	matt
C18167_DAISY-7X1-SHD-MET	Shade	PC	metal	gloss


ORDERING INFORMATION:

Quantities for one set:

Linear lens	1
Shade	1








Component		Qty in box	MOQ	MPQ	Box weight (kg)
C17362_DAISY-7X1-W-D	Linear lens	312	192	24	6.3
» Box size: 400 x 300 x 300 mm					
C17051_DAISY-7X1-SHD-MATT	Shade	156	192	24	6.7
» Box size: 595 x 360 x 230 mm					
C18167_DAISY-7X1-SHD-MET	Shade	156	192	24	7.0
» Box size: 595 x 360 x 230 mm					
C17225_DAISY-7X1-SHD-WHT-MATT	Shade	156	192	24	6.8
» Box size: 595 x 360 x 230 mm					
C16872_DAISY-7X1-SHD	Shade	156	192	24	6.4
» Box size: 595 x 360 x 230 mm					
C16876_DAISY-7X1-SHD-WHT	Shade	156	192	24	6.8
» Box size: 595 x 360 x 230 mm					
C17533_DAISY-7X1-SHD-MET-MATT	Shade	156	192	24	6.5
» Box size: 595 x 360 x 230 mm					



See also our general installation guide: www.ledil.com/installation_guide


PHOTOMETRIC DATA (MEASURED):

<p>AUDAX ELECTRONICS</p> <p>LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm</p> <p>FWHM / FWTM 64.0° / 90.0°</p> <p>Efficiency 88 %</p> <p>Peak intensity 0.8 cd/m</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components: C17533_DAISSY-7X1-SHD-MET-MATT</p>		
<p>AUDAX ELECTRONICS</p> <p>LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm</p> <p>FWHM / FWTM 64.0° / 90.0°</p> <p>Efficiency 90 %</p> <p>Peak intensity 0.8 cd/m</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components: C18167_DAISSY-7X1-SHD-MET</p>		
<p>AUDAX ELECTRONICS</p> <p>LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm</p> <p>FWHM / FWTM 65.0° / 92.0°</p> <p>Efficiency 89 %</p> <p>Peak intensity 0.8 cd/m</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components: C17225_DAISSY-7X1-SHD-WHT-MATT</p>		
<p>AUDAX ELECTRONICS</p> <p>LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm</p> <p>FWHM / FWTM 63.0° / 88.0°</p> <p>Efficiency 77 %</p> <p>Peak intensity 0.8 cd/m</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components: C17051_DAISSY-7X1-SHD-MATT</p>		


PHOTOMETRIC DATA (MEASURED):





LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
 FWHM / FWTM 65.0° / 92.0°
 Efficiency 90 %
 Peak intensity 0.8 cd/m
 LEDs/each optic 4
 Light colour White
 Required components:
 C16876_DAISY-7X1-SHD-WHT





LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
 FWHM / FWTM 64.0° / 89.0°
 Efficiency 78 %
 Peak intensity 0.8 cd/m
 LEDs/each optic 4
 Light colour White
 Required components:
 C16872_DAISY-7X1-SHD



LED LUXEON 2835 Line
 FWHM / FWTM 63.0° / 88.0°
 Efficiency 77 %
 Peak intensity 0.8 cd/m
 LEDs/each optic 4
 Light colour White
 Required components:
 C17051_DAISY-7X1-SHD-MATT



LED LUXEON 2835 Line
 FWHM / FWTM 65.0° / 93.0°
 Efficiency 90 %
 Peak intensity 0.8 cd/m
 LEDs/each optic 4
 Light colour White
 Required components:
 C16876_DAISY-7X1-SHD-WHT



PHOTOMETRIC DATA (MEASURED):


LUMILEDS

LED LUXEON 2835 Line
 FWHM / FWTM 64.0° / 89.0°
 Efficiency 78 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C16872_DAISSY-7X1-SHD





LUMILEDS

LED LUXEON 2835 Line
 FWHM / FWTM 64.0° / 91.0°
 Efficiency 88 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17533_DAISSY-7X1-SHD-MET-MATT





LUMILEDS

LED LUXEON 2835 Line
 FWHM / FWTM 64.0° / 90.0°
 Efficiency 90 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17532_DAISSY-7X1-SHD-MET



LUMILEDS



LED LUXEON 2835 Line
 FWHM / FWTM 65.0° / 92.0°
 Efficiency 89 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT



PHOTOMETRIC DATA (MEASURED):



MST *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V Opt G1
 FWHM / FWTM 64.0° / 92.0°
 Efficiency 87 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17533_DAISSY-7X1-SHD-MET-MATT




MST *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V Opt G1
 FWHM / FWTM 64.0° / 91.0°
 Efficiency 88 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C18167_DAISSY-7X1-SHD-MET




MST *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V Opt G1
 FWHM / FWTM 65.0° / 93.0°
 Efficiency 88 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT



MST *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V Opt G1
 FWHM / FWTM 64.0° / 89.0°
 Efficiency 76 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17051_DAISSY-7X1-SHD-MATT



PHOTOMETRIC DATA (MEASURED):


MST *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V Opt G1
 FWHM / FWTM 64.0° / 89.0°
 Efficiency 77 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C16872_DAISSY-7X1-SHD





MST *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V Opt G1
 FWHM / FWTM 65.0° / 93.0°
 Efficiency 88 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C16876_DAISSY-7X1-SHD-WHT





MST *Your solutions*

LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V Opt G1
 FWHM / FWTM 65.0° / 92.0°
 Efficiency 87 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour Tunable White
 Required components:
 C17533_DAISSY-7X1-SHD-MET-MATT



MST *Your solutions*


LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V Opt G1
 FWHM / FWTM 65.0° / 91.0°
 Efficiency 89 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour Tunable White
 Required components:
 C18167_DAISSY-7X1-SHD-MET



PHOTOMETRIC DATA (MEASURED):


MST *Your solutions*

LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V Opt G1
 FWHM / FWTM 66.0° / 94.0°
 Efficiency 89 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour Tunable White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT





MST *Your solutions*

LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V Opt G1
 FWHM / FWTM 65.0° / 90.0°
 Efficiency 76 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour Tunable White
 Required components:
 C17051_DAISSY-7X1-SHD-MATT




MST *Your solutions*

LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V Opt G1
 FWHM / FWTM 66.0° / 94.0°
 Efficiency 89 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour Tunable White
 Required components:
 C16876_DAISSY-7X1-SHD-WHT



MST *Your solutions*


LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V Opt G1
 FWHM / FWTM 65.0° / 90.0°
 Efficiency 77 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour Tunable White
 Required components:
 C16872_DAISSY-7X1-SHD




PHOTOMETRIC DATA (MEASURED):





LED NF2W757G-MT (Tunable White)
 FWHM / FWTM 62.0° / 86.0°
 Efficiency 93 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 1
 Light colour Tunable White
 Required components:
 C16876_DAISY-7X1-SHD-WHT





LED NF2W757G-MT (Tunable White)
 FWHM / FWTM 61.0° / 84.0°
 Efficiency 82 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 1
 Light colour Tunable White
 Required components:
 C16872_DAISY-7X1-SHD



LED LM28xB Series
 FWHM / FWTM 62.0° / 88.0°
 Efficiency 92 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 2
 Light colour White
 Required components:
 C16876_DAISY-7X1-SHD-WHT





LED LM28xB Series
 FWHM / FWTM 61.0° / 85.0°
 Efficiency 82 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 2
 Light colour White
 Required components:
 C16872_DAISY-7X1-SHD



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LM28xB Series
 FWHM / FWTM 60.0° / 84.0°
 Efficiency 77 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 2
 Light colour White
 Required components:
 C17051_DAISY-7X1-SHD-MATT




SEITEC

LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
 FWHM / FWTM 63.0° / 91.0°
 Efficiency 90 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17533_DAISY-7X1-SHD-MET-MATT





SEITEC

LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
 FWHM / FWTM 64.0° / 90.0°
 Efficiency 91 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C18167_DAISY-7X1-SHD-MET











SEITEC







LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
 FWHM / FWTM 65.0° / 93.0°
 Efficiency 91 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17225_DAISY-7X1-SHD-WHT-MATT



PHOTOMETRIC DATA (MEASURED):

<p>SEITEC Elektronik GmbH</p> <p>LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1) FWHM / FWTM 64.0° / 89.0° Efficiency 77 % Peak intensity 0.8 cd/lm LEDs/each optic 4 Light colour White Required components: C17051_DAISY-7X1-SHD-MATT</p>		
<p>SEITEC Elektronik GmbH</p> <p>LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1) FWHM / FWTM 65.0° / 93.0° Efficiency 90 % Peak intensity 0.8 cd/lm LEDs/each optic 4 Light colour White Required components: C16876_DAISY-7X1-SHD-WHT</p>		
<p>SEITEC Elektronik GmbH</p> <p>LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1) FWHM / FWTM 64.0° / 89.0° Efficiency 78 % Peak intensity 0.7 cd/lm LEDs/each optic 4 Light colour White Required components: C16872_DAISY-7X1-SHD</p>		
<p>TEPCOMP group</p> <p>LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC FWHM / FWTM 70.0° / 100.0° Efficiency 87 % Peak intensity 0.6 cd/lm LEDs/each optic 4 Light colour White Required components: C16876_DAISY-7X1-SHD-WHT</p>		


PHOTOMETRIC DATA (MEASURED):

<p>TEPCOMP group</p> <p>LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC</p> <p>FWHM / FWTM 68.0° / 93.0°</p> <p>Efficiency 71 %</p> <p>Peak intensity 0.6 cd/m</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components: C16872_DAISSY-7X1-SHD</p>		
<p>TEPCOMP group</p> <p>LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC</p> <p>FWHM / FWTM 70.0° / 100.0°</p> <p>Efficiency 87 %</p> <p>Peak intensity 0.6 cd/m</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components: C17225_DAISSY-7X1-SHD-WHT-MATT</p>		
<p>TEPCOMP group</p> <p>LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC</p> <p>FWHM / FWTM 68.0° / 94.0°</p> <p>Efficiency 71 %</p> <p>Peak intensity 0.6 cd/m</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components: C17051_DAISSY-7X1-SHD-MATT</p>		
<p>TRIDONIC</p> <p>LED LLE 24x280mm 750lm 8x0 LVD ADV1</p> <p>FWHM / FWTM 66.0° / 95.0°</p> <p>Efficiency 89 %</p> <p>Peak intensity 0.7 cd/m</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components: C16876_DAISSY-7X1-SHD-WHT</p>		

PHOTOMETRIC DATA (MEASURED):



TRIDONIC

LED LLE 24x280mm 750lm 8x0 LVD ADV1
 FWHM / FWTM 65.0° / 90.0°
 Efficiency 76 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C16872_DAISSY-7X1-SHD





TRIDONIC

LED LLE 24x280mm 750lm 8x0 LVD ADV1
 FWHM / FWTM 66.0° / 95.0°
 Efficiency 89 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT



TRIDONIC


LED LLE 24x280mm 750lm 8x0 LVD ADV1
 FWHM / FWTM 65.0° / 90.0°
 Efficiency 76 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17051_DAISSY-7X1-SHD-MATT




PHOTOMETRIC DATA (SIMULATED):




LED J Series 2835
 FWHM / FWTM 62.0° / 90.0°
 Efficiency 78 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C16872_DAISSY-7X1-SHD




LED OSLOM PURE 1010
 FWHM / FWTM 50.0° / 76.0°
 Efficiency 86 %
 Peak intensity 1.3 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT



LED LM101B
 FWHM / FWTM 54.0° / 78.0°
 Efficiency 86 %
 Peak intensity 1.1 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT




LED LM101B
 FWHM / FWTM 58.0° / 82.0°
 Efficiency 88 %
 Peak intensity 1 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C18167_DAISSY-7X1-SHD-MET



PHOTOMETRIC DATA (SIMULATED):


SAMSUNG

LED LM301Z Plus
 FWHM / FWTM 62.0° / 86.0°
 Efficiency 88 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C18167_DAISSY-7X1-SHD-MET




SAMSUNG

LED LM301Z Plus
 FWHM / FWTM 60.0° / 86.0°
 Efficiency 86 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT




SAMSUNG

LED LM301Z Plus
 FWHM / FWTM 60.0° / 86.0°
 Efficiency 75 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C17051_DAISSY-7X1-SHD-MATT





SEOUL SEMICONDUCTOR

LED SEOUL DC 3030C
 FWHM / FWTM 62.0° / 88.0°
 Efficiency 80 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:
 C16872_DAISSY-7X1-SHD



PHOTOMETRIC DATA (SIMULATED):

<p> SEOUL SEMICONDUCTOR</p> <p>LED: SEOUL DC 3528 FWHM / FWTM: 59.0° / 84.0° Efficiency: 76 % Peak intensity: 0.8 cd/lm LEDs/each optic: 1 Light colour: White Required components: C16872_DAISSY-7X1-SHD</p>	
<p>TRIDONIC</p> <p>LED: LLE 24x280mm 750lm 8x0 LVD ADV1 FWHM / FWTM: 62.0° / 88.0° Efficiency: 88 % Peak intensity: 0.9 cd/lm LEDs/each optic: 4 Light colour: White Required components: C17533_DAISSY-7X1-SHD-MET-MATT</p>	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)